



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

0928174 VBX3384 BJAA LT PARCHMENT

Version Number 1.2
Revision Date 05/14/2008

Page 1 of 6
Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Product name : 0928174 VBX3384 BJAA LT PARCHMENT
Product code : FO00000295
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Particulates, like other inert materials can be mechanically irritating.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

0928174 VBX3384 BJAA LT PARCHMENT

Version Number 1.2
Revision Date 05/14/2008

Page 2 of 6
Print Date 1/3/2012

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : Not applicable
- Flammable Limits
Upper explosion limit : Not applicable
Lower explosion limit : Not applicable
- Autoignition temperature : Not relevant
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

0928174 VBX3384 BJAA LT PARCHMENT

Version Number 1.2
 Revision Date 05/14/2008

Page 3 of 6
 Print Date 1/3/2012

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m ³	Time Weighted Average (TWA):		ACGIH
	15 mg/m ³	PEL:	Total dust.	OSHA Z1
	10 mg/m ³	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m ³	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Solid
- Appearance : powder, granular
- Color : WHITE
- Odour : Very faint
- Melting point/range : Not determined
- Boiling Point: : Not applicable
- Water solubility : Insoluble
- Evaporation rate : Not applicable
- Specific Gravity : Not determined
- Bulk density : Not determined
- Vapour pressure : Not applicable
- Vapour density : Not applicable
- pH : Not applicable

10. STABILITY AND REACTIVITY

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

0928174 VBX3384 BJAA LT PARCHMENT

Version Number 1.2
Revision Date 05/14/2008

Page 4 of 6
Print Date 1/3/2012

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.

Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Adverse ecological impact is not known or expected under normal



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

0928174 VBX3384 BJAA LT PARCHMENT

Version Number 1.2
Revision Date 05/14/2008

Page 5 of 6
Print Date 1/3/2012

use.

Bioaccumulation Potential : No data available

Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA (air) : Not regulated for transportation.

IMO / IMDG (maritime) : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****0928174 VBX3384 BJAA LT PARCHMENT**Version Number 1.2
Revision Date 05/14/2008Page 6 of 6
Print Date 1/3/2012

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc stearate	557-05-1	0.10 - 1.00	
Miscellaneous Zinc Compounds	0-31-7	0.10 - 1.00	241

WHMIS Classification : D2A

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.