



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

2200030 VBX3340 F24S GRAY AC20615 PWD

Version Number 1.0
Revision Date 10/10/2003

Page 1 of 7
Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship (314) 771-1800
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : 2200030 VBX3340 F24S GRAY AC20615 PWD
Product code : FO00011090
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Particulates, like other inert materials can be mechanically irritating.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****2200030 VBX3340 F24S GRAY AC20615 PWD**

Version Number 1.0

Revision Date 10/10/2003

Page 2 of 7

Print Date 11/12/2011

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

- Upper explosion limit** : Not applicable
- Lower explosion limit** : Not applicable

Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

2200030 VBX3340 F24S GRAY AC20615 PWD

Version Number 1.0
Revision Date 10/10/2003

Page 3 of 7
Print Date 11/12/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
- Eye/Face Protection : safety glasses with side-shields
- Hand protection : protective gloves
- Skin and body protection : long sleeved clothing
- Additional Protective Measures : safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Solid
- Appearance : powder, granular
- Color : GREY
- Odor : Very faint
- Melting point/range : Not determined
- Boiling Point: : Not applicable
- Water solubility : Insoluble
- Evaporation rate : Not applicable
- Specific Gravity : Not determined
- Bulk density : Not determined
- Vapor pressure : Not applicable
- Vapour density : Not applicable
- pH : Not applicable

10. STABILITY AND REACTIVITY

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

2200030 VBX3340 F24S GRAY AC20615 PWD

Version Number 1.0
Revision Date 10/10/2003

Page 4 of 7
Print Date 11/12/2011

- Stability : Stable.
- Hazardous Polymerization : Will not occur.
- Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
- Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****2200030 VBX3340 F24S GRAY AC20615 PWD**Version Number 1.0
Revision Date 10/10/2003Page 5 of 7
Print Date 11/12/2011

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA (air) : Not regulated for transportation.
- IMO / IMDG (maritime) : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

2200030 VBX3340 F24S GRAY AC20615 PWD

Version Number 1.0
Revision Date 10/10/2003

Page 6 of 7
Print Date 11/12/2011

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable
Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

2200030 VBX3340 F24S GRAY AC20615 PWD

Version Number 1.0
Revision Date 10/10/2003

Page 7 of 7
Print Date 11/12/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.